(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 28 April 2005 (28.04.2005)

PCT

(10) International Publication Number WO 2005/038700 A1

(51) International Patent Classification⁷:

G06K 9/62

(21) International Application Number:

PCT/EP2004/052502

(22) International Filing Date: 11 October 2004 (11.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0323662.7

9 October 2003 (09.10.2003) GB GB

17 April 2004 (17.04.2004) 0408570.0

(71) Applicant (for all designated States except US): University of York [GB/GB]; Heslington, YORK Yorkshire YO1 5DD (GB).

(72) Inventors; and


(75) Inventors/Applicants (for US only): AUSTIN, James [GB/GB]; Corner House Farm, Fimber, Driffield Yorkshire YO25 9LY (GB). PEARS, Nicholas [GB/GB]; 6, Howard

Street, YORK Yorkshire YO10 4BQ (GB). HESELTINE, Thomas [GB/GB]; 29, Anchor Court, Cartway, Bridgnorth Shropshire WV16 4BG (GB).

- (74) Agent: STANLEY, David; STANLEYS, Kings Court, 12 King Street, LEEDS Yorkshire LS1 2HL (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: IMAGE RECOGNITION



Identification System

(57) Abstract: A camera A produces a 3D natural image B which is re-oriented and repositioned at N to predetermined parameters. Different processes C, D, E extract different features from the image to provide different processed images. The data space occupied by the processed images is reduced, for example by Principle Component Analysis, at F, G, H and the reduced processed images are combined at O to provide an image key I representative of the image B. The image key I is compared at J with stored image keys L of known images, and the output comparison is sorted at K to produce a final list M of potential matches. In a verification process, just a single image key L may be compared. The processed images at C, D. E may alternatively be combined prior to a single subspace reduction and/or optimisation method. 2D data may be combined with or used instead of the 3D data.

5/038700

WO 2005/038700 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.